


# Auxiliaries

## IC – 800 Degreaser

**Product Description**  
 IC-800 are particularly well suited for removing grease, oils, wax and silicone prior to the application of InnoColor primer and for the pre-treatment of plastic surfaces.

**Technical Characteristics**  
 Color: transparent      Shelf life: 48 months at 25°C

**Pre-treatment**  
 Do not use the cleaners on solvent-sensitive or thermoplastic substrates.

	<b>Mixing Ratio</b>	<p>This product is ready for use</p> <p>Soak a clean and dry lint-free cloth with IC-800</p>
	<b>Application</b>	<p>Degrease small areas of approximately 0.5 m<sup>2</sup> of the surface to be painted and wipe these areas immediately afterwards with a dry cloth of the same quality.</p>
<b>Further Treatment</b>		<p>IC-800 should not dry on the surface being treated.</p> <p><b>Attention:</b>        Some 1K primers/basecoats may suffer surface etching from the use of IC-800. In this case, ensure a good flash-off of the substrate before going on with the repair so that no solvents will be trapped in the new paint system. In extreme cases, remove the 1K primer/basecoat before applying the new paint system, or flat with P800-1000 grade sandpaper for refining refinish.</p>
		<p>As specified in the InnoColor refinishing processes.</p>

The products are suitable for professional use only. The data contained in this publication are based on our current knowledge and experience. You can obtain the latest version of technical data sheet from our website at [www.wonder-global.com](http://www.wonder-global.com) or directly from your supplier.